

# 4CH PoE NVR

## NVR5-4100PX+(MM)



**5MP**



MODEL	NVR5-4100PX+(MM)	
Video	Input	4CH RJ45 Direct Connection / Over Network
	Output	HDMI / VGA (1080P, 1280x1024, 1024x768)
	Decoding Format	H.265 / H.264
	Decoding Capabilities	1Ch - 5MP ; 4Ch - D1
	Analytics	Camera Tampering, Line Crossing, Sterile Area, Object Monitoring
Audio	Input	Depends on Camera Inputs
	Output	Depends on Camera Outputs
	Two Way Audio	No
Bandwidth	Incoming	24Mbps
	Outgoing	24Mbps
Recording	Real-Time Recording	4CH 5MP Real-Time
	8MP	No
	5MP	120FPS (NTSC)/100FPS (PAL)
	4MP	120FPS (NTSC)/100FPS (PAL)
	3MP	120FPS (NTSC)/100FPS (PAL)
	2MP (1080P)	120FPS (NTSC)/100FPS (PAL)
	1.3MP (960P) and lower	120FPS (NTSC)/100FPS (PAL)
	Recording Modes	Schedule, Manual, Motion, Sensor, Analytics
Playback	Playback Channels	4CH
	Search Mode	Time-Slice, Time, Event, File Management
Backup	USB	2 USB 2.0 Port
	DVD Burner	No
	Backup Format	AVI/DAT
Remote Application	Master Stream	Up to 4CH@Recording Resolution
	Sub-Stream	Depends on IPC
	Browser	Safari (Mac OS) IE (Windows Vista/7/8/10)
	CMS	Yes
	Mobile Application	Provision CAM2 for iOS/Android
	User Access	10 Users Online with Professional Authority Management
Alarm	Input	Depends on Camera
	Output	Depends on Camera
Storage	HDD	1 SATA (6TB)
	E-SATA	No
PTZ	Connection	Via Network
	Supported Controls	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus
	RS-485	No
Network	Ethernet	100 Mbps (RJ-45)
	Protocol	TCP/IP, DHCP, DDNS, NTP, SMTP, P2P, RTSP
	ONVIF	Yes
PoE	Ports	Yes (4CH)
	Interface	10/100Mbps
	Standard	IEEE802.3AF
	Total Power	50W (Average 12.5W per Channel)
	Max. Power Output (Per Ch.)	~14W
Others	Power Supply	DC48V/1.04A
	Power Consumption (No HDD)	5W
	Dimension	W255xD220xH45mm
	Operation Temperature	0°C ~50°C