

1CH HD VIDEO PASSIVE BALUN

PTR-101V-HD+



MODEL	PTR-101V-HD+	
Input	1Ch x Twisted Pair	
Output	1Ch BNC	
System Format	PAL / NTSC	
Input Resolution Support	5MP and Lower	
Input Signal Support	4 in 1 (AHD / CVI / TVI / CVBS)	
Transmission Distance	5/4MP	200m (AHD) / 150m (CVI / TVI)
	2MP	200m (AHD) / 150m (CVI / TVI)
	1MP	200m (AHD) / 150m (CVI / TVI)
	960H and Lower	200m
Attenuation	1.5db Max	
Wiring	Unshielded Twisted Pair	
Surge Protection	2KV	
Work Environment	-20°C-70°C, 0%-90% Humidity	
Power Source	Not Required (Passive Unit)	
Dimenstions	Camera Side - 51x19x18mm / DVR Side - 40x20x18mm + 140mm Wire	
Net Weight	30g	

Main Features:

- 1Ch Set
- 5MP 4in1 support: AHD / CVI / TVI / CVBS
- Passive - No Power Required
- Minimal Attenuation
- Light Weight

1CH HD VIDEO + POWER PASSIVE BALUN

PTR-102VP-HD+



MODEL	PTR-102VP-HD+	
Input	1Ch BNC + 12VDC Power	
Output	1Ch BNC + 12VDC Power	
System Format	PAL / NTSC	
Input Resolution Support	5MP and Lower	
Input Signal Support	4 in 1 (AHD / CVI / TVI / CVBS)	
Transmission Distance	5/4MP	200m (AHD) / 150m (CVI / TVI)
	2MP	200m (AHD) / 150m (CVI / TVI)
	1MP	200m (AHD) / 150m (CVI / TVI)
	960H and Lower	200m
Attenuation	1.5db Max	
Wiring	Cat5/5e/6 crimped cable (RJ-45)	
Surge Protection	2KV	
Work Environment	-20°C-70°C, 0%-90% Humidity	
Power Source	Not Required (Passive Unit). Power is required for powered device only.	
Dimenstions	Camera/DVR Side - 73x29x20mm + 113mm Wire	
Net Weight	60g	

Main Features:

- 1Ch Set
- 5MP 4in1 support: AHD / CVI / TVI / CVBS
- Passive
- Minimal Attenuation
- Light Weight

Power transmission max. distance

Model Consumption	Power Supply	
	DC 12V	DC 15V
200mA	180m	280m
300mA	120m	180m
400mA	100m	130m
500mA	80m	110m
600mA	60m	90m